



NIGE

RGB LED full colour

NIGE 1

WALL WASHER RGB CON LED ALTA POTENZA PER INTERNO – L = 50 cm

Whall Washer orientabile L = 50 cm.

6 LED da 3 W.

Alimentazione: 220-240 VAC / 50-60 Hz.

Consumo: 18 W.

Da utilizzarsi con modulo controllo colore cod. QR/RGB (pg. 194) per una sola unità.

Sistema DMX-S1 (pg. 196) o DMX-S4 (pg. 202) per sincronia colore di più unità.

Installazione

Tramite staffa orientabile compresa nella fornitura.

WALL WASHER RGB HIGH POWER LINEAR LIGHTING PROFILE – L = 50 cm

Adjustable Wall Washer L = 50 cm.

6 LEDs 3 W.

Voltage input: 220-240 VAC / 50-60 Hz




Consumption: 18 W.

To be used with colour control module cod. QR/RGB (pg. 194) for just Nr. 1 spot.

To be used with DMX-S1 (pg. 196) or DMX-S4 (pg. 202) for more than Nr. 1 spot.

Installation

Adjustable support included.



FINITURA / FINISHING

COLORE LED / LED COLOUR

01 03 04 FOCAL / BEAM SPREAD

670-01- GR 99

CODICE / CODE

NIGE 2

WALL WASHER RGB CON LED ALTA POTENZA PER INTERNO – L = 100 cm

Whall Washer orientabile L = 100 cm.

12 LED da 3 W.

Alimentazione: 220-240 VAC / 50-60 Hz.

Consumo: 36 W.

Da utilizzarsi con modulo controllo colore cod. QR/RGB (pg. 194) per una sola unità.

Sistema DMX-S1 (pg. 196) o DMX-S4 (pg. 202) per sincronia colore di più unità.

Installazione

Tramite staffa orientabile compresa nella fornitura.

WALL WASHER RGB HIGH POWER LINEAR LIGHTING PROFILE – L = 100 cm

Adjustable Wall Washer L = 100 cm.

12 LEDs 3 W.

Voltage input: 220-240 VAC / 50-60 Hz

Consumption: 36 W.



To be used with colour control module cod. QR/RGB (pg. 194) for just Nr. 1 spot.

To be used with DMX-S1 (pg. 196) or DMX-S4 (pg. 202) for more than Nr. 1 spot.

Installation

Adjustable support included.



NIGE 1 (670-01)



CE | IP40



NIGE 2 (671-02)



DIMENSIONI / DIMENSIONS

FINITURA / FINISHING

COLORE LED / LED COLOUR

01 03 04 FOCAL / BEAM SPREAD

671-02- GR 99

CODICE / CODE