

## DUBRIS 3

### FARETTO ORIENTABILE con 1 LED da 1 W

Alimentazione: in corrente continua 350 mA.

Collegamento in serie.

Consumo: 1,4 W.

Alimentatore consigliato: cod. TRDC/350mA (pg. 185).

#### Installazione

Tramite viti.

### ADJUSTABLE SPOTLIGHT with 1 LED 1 W

Supply current: 350 mA constant.




Serial connection.

Consumption: 1.4 W.

Led power supply: code TRDC/350mA (pg. 185).

#### Installation


By screws.



CR	GR	OR	FINITURA / FINISHING			
00	10	20	30	40	50	COLORE LED / LED COLOUR
06	08	FOCALE / BEAM SPREAD				

423-03-

CODICE / CODE



DIMENSIONI / DIMENSIONS

## DUBRIS 4

### FARETTO ORIENTABILE con 1 LED da 3 W

Alimentazione: in corrente continua 700 mA.

Collegamento in serie.

Consumo: 3,2 W.

Alimentatore consigliato: cod. TRDC/700mA (pg. 187).

#### Installazione

Tramite viti.

### ADJUSTABLE SPOTLIGHT with 1 LED 3 W

Supply current: 700 mA constant.




Serial connection.

Consumption: 3.2 W.

Led power supply: code TRDC/700mA (pg. 187).

#### Installation


By screws.



CR	GR	OR	FINITURA / FINISHING			
00	10	20	30	40	50	COLORE LED / LED COLOUR
06	08	FOCALE / BEAM SPREAD				

425-04-

CODICE / CODE



DIMENSIONI / DIMENSIONS